

Cutting-off wheel

C 24 EXTRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Silicon carbide
Bond	■■■■□□□
Aggression	■■■■□□□
Service life	■■■■□□□

Product benefit

Universal cutting-off wheel for all mineral materials - Wide application range due to sharp, coarse SiC grit

Materials

Stone/Concrete ●

Applications

- Gardening and landscaping
- Stonemason businesses

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 2,5 x 16		80 m/s	15300 rpm	25	188999
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	242143
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	188462
125 x 2,5 x 22,23		80 m/s	12200 rpm	25	242144
125 x 2,5 x 22,23		80 m/s	12200 rpm	25	188464
180 x 3 x 22,23		80 m/s	8500 rpm	25	13489
230 x 3 x 22,23		80 m/s	6600 rpm	25	13491
230 x 3 x 22,23		80 m/s	6600 rpm	25	189003

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

