

PRODUCT DATASHEET

Washed SuperTEK 7 Range



Product Details

Purpose:	Fixing steel to steel
Head style:	5/16" Hexagonal Head
Drill Point:	TEK 7 spiral point
Thread Form:	Single, 24 threads per inch fine thread 'V' fluted
Coating:	1000hr Rated EvoShield® Coating
Shank Material:	Carbon Steel
Material Grade:	AISI C1022
Recommended Drill Speed:	1,500 - 2,500 RPM

Washed SuperTEK 7 Range - Products for use in Heavy Gauge Steel Applications (4.0mm to 18.5mm mild steel)

SKU	Nominal Dimensions, dnom x Lnom (mm)	Effective Thread Length, Lthread (mm)	Drilling Capacity, Hcap (mm)
TSBW5.5-50-7	5.5 x 50.0	Full	4.0 - 18.5

Ultimate Withdrawal Resistance, N_{Rk} , from S355JR Steel (N)

Diameter	Nominal Substrate Thickness, t_{nom}					
	4.0mm	6.0mm	8.0mm	10.0mm	15.0mm	18.0mm
5.5mm	4,100 N	6,900 N	11,300 N	13,500 N	16,600 N	19,700 N

Ultimate Mechanical Performance

Property	Magnitude
Tensile Capacity, (F_{ult}, R_k)	13,900N
Shear Capacity, (V_{ult}, R_k)	10,300N

NOTE: The results expressed in this document are determined from empirical testing. Specifiers, end-users and other third parties should make their own decision(s) on what safety factors to use relevant to their design(s)/ application(s). This document is provided, strictly: without prejudice, without recourse, without liability, non-assumpsit, no assured value, errors and omissions excepted, subject to change without notice and all rights reserved.
 ©Evolution Fasteners UK Ltd, 2021.