

C: Newtown Packaging Ltd
A: 80 Arthur Street, Redditch, Worcestershire, B98 8JY
T: +44 (0) 1527 517 517
E: sales@newtownpackaging.com

PRODUCT – NP1245.03 SERIES
PRODUCT GROUP – Protective Tapes

Application:

Is suitable for carpets, printed textiles, or any such woven cloth surfaces that require temporary protection during installation, storage and transportation.
 NP1245.03 series exhibits excellent puncture and tear resistance. The adhesive backing maintains a smooth walk surface without lifting of edges



PRODUCT SPECIFICATION:

Film Type	Polyethylene (LDPE) UV Treated
Color	Clear Printed Green
Average Thickness (A.S.T.M)	40-50 Mic
Adhesive Type	Acrylic Adhesive
Adhesion to Steel (A.S.T.M)	350gm/25.4mm (Gm/mm)
Longitudinal Tensile Strength (A.S.T.M)	>3.5kg/25.4mm (Kg/mm)
Transversal Tensile Strength (A.S.T.M)	>2.0kg/25.4mm (kg/mm)
Longitudinal Max Elongation (A.S.T.M)	>350 (%)
Transversal Max Elongation (A.S.T.M)	>570 (%)

(American Standard Test Method- A.S.T.M)

Storage & Utilization

The tape can be stored for 12 months in dry conditions in its original packaging. The film should be removed within 3 months from the date of lamination, particularly if the product has been exposed to outdoor ageing.

DISCLAIMER:

- Due to the variety of different materials available on the markets pre-tests should be carried out. We suggest to our customers an evaluation trial to confirm the suitability use of this product
- NEWTOWN is not responsible for misuse of this product, nor for the consequences of improper application.
- All information in this data sheet is given in good faith on the basis of practical experience.

