

Technical Specification Sheet



Antinox® FR Protection Board

Features

Antinox® is a range of protection boards for use in areas for impact resistance on floors, walls, windows, columns and other surfaces that may be damaged by general site activity. Simply and quickly cut, curved or creased, approved by MOD and Civil Aviation Authority, available in numerous colours.

Benefits

The main benefits of Antinox® protection boards are focused on the twin skin corrugation which enhances its impact resistance properties. Combined with its easy to handle characteristics this produces an effective system of water resistant, impact resistant temporary protective sheeting.

Supply

Antinox® is available in sheets and rolls for direct delivery to site or yard. Custom printing is available for larger quantities, special sizes can also be produced.

Specification

Grade	2/250	3/350	3/450	4/650	4/900	6/1400
Product code	131225	131227	131231	131230	131228	131229
Thickness	2mm	3mm	3mm	4mm	4mm	6mm
Weight	250gsm	350gsm	450gsm	650gsm	900gsm	1400gsm
Material	Polypropylene	Polypropylene	Polypropylene	Polypropylene	Polypropylene	Polypropylene
Sheet size	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m
Colour	White or Black	White	White	White	White	White
Flame Retardancy	LPS 1207 Certifire TS63	LPS 1207 Certifire TS63	LPS 1207 Certifire TS63	LPS 1207 Certifire TS63	LPS 1207 Certifire TS63	LPS 1207 Certifire TS63

*Also available in sheets 2.0m x 1.0m, 1.2m x 1.2m and rolls 50m x 1m - Available in white