

# Technical Specification Sheet



## Antinox® Non FR Protection Board

### Features

Antinox® is a range of protection boards for use in areas for impact resistance on floors, walls, windows, columns and other surfaces that may be damaged by general site activity. Flame retardant grades are available to suit a variety of applications.

### Benefits

The main benefits of Antinox® protection boards are focused on the twin skin corrugation which enhances its impact resistance properties. Combined with its easy to handle characteristics this produces an effective system of water resistant, impact resistant temporary protective sheeting.

### Supply

Antinox® is available in sheets and rolls for direct delivery to site or yard. Custom printing is available for larger quantities, special sizes can also be produced.

Specification						
Grade	2/250*	3/350	3/450	4/650	4/900	6/1450
Product code	132335	132331	132337	132338	132340	132341
Thickness	2mm	3mm	3mm	4mm	4mm	6mm
Weight	250gsm	350gsm	450gsm	650gsm	900gsm	1450gsm
Material	Polypropylene	Polypropylene	Polypropylene	Polypropylene	Polypropylene	Polypropylene
Sheet size	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m	2.4m x 1.2m
Colours	Black/Trans	Black	Trans	Trans	Trans	Trans
Application	Light	Medium	Medium	Medium	Heavy	Very Heavy
*Also available in sheets 2.0m x 1.0m, 1.2m x 1.2m and rolls 50m x 1m						

These properties are the manufacturer's typical values based on the average of several tests. As the installation and handling of this product are beyond our control, the user must ensure that the product is suitable for the application. Swiftec Group cannot accept responsibility for any loss or damage that may occur either directly or indirectly by the use of this product. Swiftec Group also hold the right to change specification data with out prior notice. E & OE.