Technical Data Sheet	Title: 0043 cloth tape	
Effective Date: Jan 2020	Prepared By: Sam Murphy	1
Issue Number: 13	Authorised By: Robin lamb	
		0.01



Product Description

A polyethylene laminated cloth tape coated with a strong synthetic rubber adhesive.

Applications

Designed as a general purpose cloth tape for a full range of industrial and construction applications such as sealing, insulating, repairs, masking and bundling.

Features & Benefits

Good water resistance Good adhesion and strength Flexible and conformable Low moisture vapour transmission

Technical Performance

Description	Units	Value	Test Method
Total thickness	mm	0.17	PSTC-133
Peel adhesion	N/25mm	>15	PSTC-101
Tensile strength	N/25mm	75	PSTC-131
Rolling tack Ball 11mm	cm	≤20	PSTC-106
Service temperature	°C	-20 to + 80	-
Ideal application Temp	°c	+10 - + 40	-

Declaration of Conformity Information

Chlorine & Sulphur free

REACH SVHC Status

NO SHVC present according to candidates list of the UK 25/06/20 & EU 23/01/24

RoHS Compliance Status

N/A

Storage Details

Store in moderate temperature and humidity environment.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/08/17)