

DrillTech CSLSW - light section wing-tip self-drilling screw

Technical Data Sheet




Typical Applications

- Fixing timber battens to light duty steel sections.
- General timber to steel applications.
- Fixing sheathing boards to steel.

Product Information

Size (mm)	Drill Point	Drilling Capacity (mm)	Head Style	Drive	Finish
4.2 x 25	2pt	1.2 - 3.0	Csk	PH2	BZP
4.8 x L	3pt	1.2 - 4.0	Csk	PH2	BZP
5.5 x L	3pt	1.2 - 5.0	Csk	PH3	BZP



Ultimate Pullout Strength, kN

Diameter (mm)	Drill Point	Nominal Steel Thickness			
		1.2mm	2.0mm	3.0mm	5.0mm
4.2	3pt	1.4	2.8	4.2	-
4.8	3pt	1.4	3.0	5.1	12.4
5.5	3pt	1.4	2.7	5.2	13.2

Ultimate Shear Strength, kN

Diameter (mm)	Drill Point	Nominal Steel Thickness			
		1.2mm	2.0mm	3.0mm	5.0mm
4.2	3pt	-	4.1	5.1	-
4.8	3pt	4.2	-	-	6.0
5.5	3pt	4.8	-	-	9.0

Ultimate Mechanical Strength, kN

Diameter (mm)	Drill Point	Ultimate Tensile Strength (kN)	Ultimate Shear Strength (kN)
4.8	3pt	12.1	14.9
5.5	3pt	17.3	19.5

- Pullout tests conducted by VJT Test Laboratory using in-house test method VJTTLSP14 based on the latest CFA guidance note (method available on request).
- Pullover tests conducted following the principles of BS 5427:2016+A1:2017 (Code of practise for the use of profiled sheet for roof and wall cladding on buildings: Annex E). Tests conducted with 16mm washer fitted under screw head.
- Ultimate tensile tests conducted generally in accordance with ISO 16892-1
- Ultimate shear tests conducted generally in accordance with Mil Std 1312-13
- Performance data is unfactored.

Features & Benefits

- Winged tip creates clearance hole in timber - designed to avoid jacking
- Wings break off on contact with steel
- C1022 case-hardened carbon steel
- Coarse thread

Installation Tips

- For optimal install use a screwgun with depth setting nosepiece and RPM range of 1500-2200
- Avoid overdriving/ overtightening
- Fastener is fully seated when head is in contact with material surface
- A minimum of 3 threads must protrude through the rear of the metal structure

All product specifications and data are subject to change without notice.

The data contained in this datasheet is believed to be accurate and is reproduced in good faith. It is the customer's responsibility to ensure that the product described in this datasheet is suitable for their application.

VJ Technology disclaim any and all liability for any errors, inaccuracies or incompleteness contained in the datasheet. In addition VJ Technology makes no warranty, representation or guarantee regarding the suitability of the product described by the datasheet for any particular or associated purchase.

| V5.1 | SIN | DT | CSLSW | 25

VJ Technology Limited
Technology House, Brunswick Road,
Cobbs Wood Industrial Estate,
Ashford, Kent. TN23 1EN
t.01233 637695
e.enquiries@vjtechnology.com
www.vjtechnology.com