



Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Reference nr: 230082

Unique identification code of the product-type

Soudaflex 40FC

Intended use or uses of the construction product

**Sealants for facade for interior and exterior application
Sealants for pedestrian walkways for interior use**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire
System 3: for essential characteristics**

Construction product in accordance with applicable harmonised specifications

**EN 15651-1:2012: Type F-EXT-INT
EN 15651-4:2012: Type PW-INT**

The notified body

The notified body GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Durability	Pass	

Conditioning: Method A

Test Substrate: aluminium, mortar

Declared Performance: EN 15651-4:2012


Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Loss of volume	≤ 10%	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Durability	Pass	

Conditioning: Method A

Test Substrate: aluminium, mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr: 230082

EN 15651-1:2012

EN 15651-4:2012

Sealants for facade for interior and exterior application

Sealants for pedestrian walkways for interior use

Soudaflex 40FC

EN 15651-1:2012: Type F-EXT-INT

EN 15651-4:2012: Type PW-INT

Conditioning: Method A

Test Substrate: aluminium, mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-4:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at maintained extension	NF	
Tear resistance	NF	
Durability	Pass	



UKCA Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

UK Reference nr DOP: 230082UK

Unique identification code of the product-type

Soudaflex 40FC

Intended use or uses of the construction product

**Sealants for facade for interior and exterior application
Sealants for pedestrian walkways for interior use**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative

**Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth
B77 5PN Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire
System 3: for essential characteristics**

Construction product in accordance with applicable designated standards

**BS EN 15651-1:2012: Type F-EXT-INT
BS EN 15651-4:2012: Type PW-INT**

Approved Body

4ward Testing, AB 2538, has carried out Determination of the Product Type under system 3.



Declared Performance: BS EN 15651-1:2012

Essential Characteristics	Performance	Designated Technical Specification
Release dangerous chemicals	NPD	BS EN 15651-1:2012
Resistance to flow	≤ 3 mm	
Water and air tightness		
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Durability	Pass	

Conditioning: Method A

Test substrate: aluminium, mortar with primer

Declared Performance: BS EN 15651-4:2012

Essential Characteristics	Performance	Designated Technical Specification
Release dangerous chemicals	NPD	BS EN 15651-4:2012
Loss of volume	NPD	
Water and air tightness		
Tensile properties at maintained extension	NF	
Tear resistance	NPD	
Durability	Pass	

Conditioning: Method A

Test substrate: aluminium, mortar with primer

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

**UK
CA**
AB 2538

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium
21
UK Reference nr DOP: 230082UK

BS EN 15651-1:2012
BS EN 15651-4:2012

Sealants for facade for interior and exterior application
Sealants for pedestrian walkways for interior use

Soudaflex 40FC

BS EN 15651-1:2012: Type F-EXT-INT
BS EN 15651-4:2012: Type PW-INT

Conditioning: Method A

Test substrate: aluminium, mortar with primer

Essential Characteristics	Performance	Designated Technical Specification
Release dangerous chemicals	NPD	BS EN 15651-1:2012 BS EN 15651-4:2012
Resistance to flow	≤ 3 mm	
Water and air tightness		
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at maintained extension	NF	
Tear resistance	NPD	
Durability	Pass	