

# DECLARATION OF PERFORMANCE

**DoP No. 0756-CPD-0290 - EN**

1. Unique identification code of the product-type:

**fischer-Zykon-Anchor FZA, FZA-D, FZA-I**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**ETA-98/0004, Annex 1 – 5**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	<b>Undercut anchor</b>
For use in	<b>Cracked and non-cracked concrete C20/25 – C50/60 (EN 206)</b>
Option / category	<b>ETAG 001 - Option 1</b>
Loading	<b>Static and quasi-static</b>
Material	<b>Zinc-plated steel:</b>
	<b>Dry internal conditions only</b> Covered sizes: <b>FZA M8, M10, M12, M16; FZA-D M8, M10, M12, M16; FZA-I M6, M8, M10, M12</b>
	<b>Stainless steel (marking A4):</b>
	<b>Internal and external use without particular aggressive conditions</b> Covered sizes: <b>FZA M8, M10, M12, M16; FZA-D M8, M10, M12, M16; FZA-I M6, M8, M10, M12</b>
	<b>Highly corrosion-resistant steel (marking C):</b>
	<b>Internal and external use with particular aggressive conditions</b> Covered sizes: <b>FZA M8, M10, M12, M16; FZA-D M8, M10, M12, M16; FZA-I M6, M8, M10, M12</b>

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**fischerwerke GmbH & Co. KG, Weinalde 14 - 18, 72178 Waldachtal, Deutschland**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): ---

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **1**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: ---

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Deutsches Institut für Bautechnik (DIBt) issued ETA-98/0004  
on the basis of ETAG 001-1, ETAG 001-3. ETAG 001 - Option 1**

**MPA Darmstadt 0756-CPD** performed

- (i) determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product;
- (ii) initial inspection of the manufacturing plant and of factory production control;
- (iii) continuous surveillance, assessment and evaluation of factory production control.

under system **1** and issued certificate of constancy of performance **0756-CPD-0290**.

9. Declared performance

Essential characteristics	Design Method	Performance	Harmonised technical specification
Characteristic resistance for tension	ETAG 001 Annex C	ETA-98/0004, Annex 8, Annex 10, Annex 12	ETAG 001-1
Characteristic resistance for shear	ETAG 001 Annex C	ETA-98/0004, Annex 9, Annex 11, Annex 13	
Minimum spacing and minimum edge distance	ETAG 001 Annex C	ETA-98/0004, Annex 8, Annex 10, Annex 12	
Displacement for serviceability limit state	ETAG 001 Annex C	ETA-98/0004, Annex 8, Annex 9, Annex 10, Annex 11, Annex 12, Annex 13	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

*i.V. W. Hengesbach*

Wolfgang Hengesbach  
Dipl.-Ing., Dipl.-Wirtsch.-Ing.  
Zulassungen & Technische Dokumente

*i.V. A. Bucher*

Andreas Bucher  
Dipl.-Ing.  
Forschung & Technologietransfer



Waldachtal, 2013-06-17