

## 0020 - Spring Toggle

### Description

The spring toggle is a metal fixing for use in hollow materials. It offers high loadings in plasterboard as the wings spread the load over a wide area. The two wings fold back to pass through the plasterboard and spring open to grip over a wide area.

### Advantages

- Large contact area provides good load-bearing properties
- Heavy gauge nut to prevent stripping
- Zinc plating
- Fire resistant
- Expands by spring force

### Typical applications


- Electrical fittings
- Ceiling fittings
- Bathroom fixtures
- Curtain rails
- Towel rails
- Pictures




### Product Range

VJT Code	Description	Screw Diameter	Screw Length (mm)	Hole Diameter (mm)	Max. Fixture Thickness (mm)	Box Qty
00200010	Spring Toggle 3 x 50	M3	50	11	30	100
00200020	Spring Toggle 5 x 50	M5	50	14	20	100
00200030	Spring Toggle 5 x 75	M5	75	14	45	50
00200035	Spring Toggle 5 x 80	M5	80	14	50	50
00200040	Spring Toggle 5 x 100	M5	100	14	70	50
00200050	Spring Toggle 6 x 75	M6	75	18	45	50
00200060	Spring Toggle Head Only M3	M3	-	11	-	100
00200070	Spring Toggle Head Only M5	M5	-	14	-	100
00200080	Spring Toggle Head Only M6	M6	-	18	-	100
00200090	Spring Toggle Head Only M8	M8	-	22	-	50
00200100	Spring Toggle Head Only M10	M10	-	25	-	50


### Installation Procedure




1. Drill the correct size hole for the toggle to pass through the base material.



2. Pass the screw through the fixture and screw the wings onto the screw.



3. Close the wings back along the length of the screw and push through the hole.



4. Tighten the screw until the fixture is secure.

## 0065 - Express Nail BZP



### Description

A steel nail for lightweight applications in masonry and concrete. The nail is hammered home and no screw or plug is required.

### Features

- All steel hammer driven anchor for rapid fixing of battens to hard materials
- Fire resistant due to all steel material
- Plated in zinc 3-5 microns

### Typical applications

- Timber battens
- Wall plates
- Sole plates

### Express Nail BZP

VJT Code	Size	Hole Size (mm)	Max Fixture Thickness (mm)	Minimum Hole Depth (mm)	Anchor Length (mm)	Box Qty
00650010	6 x 50	6	20	40	50	200
00650020	6 x 60	6	30	40	60	100
00650030	6 x 80	6	50	40	80	100
00650040	6 x 70	8	30	50	70	100
00650050	8 x 90	8	50	50	90	50
00650060	8 x 110	8	70	50	110	50
00650070	8 x 130	8	90	50	130	50
00650080	8 x 150	8	110	50	150	50