

0180 - Rigid Insulation Anchors

Description

A one piece fixing manufactured from corrosion resistant Polypropylene. The head diameter is 35mm and features a rough surface to provide a key for applied renders. Available in varying lengths to suit a wide range of insulation thicknesses and is installed into an 8mm diameter pre drilled hole.



Advantages

- Through fixing
- Hammerset (Quick & Simple)
- Corrosion proof
- One piece fixing
- 35mm diameter head
- Dimbled head to give good key for render

Typical applications

- Fixing of rigid insulation boards such as;
- EPS
 - High Density Rockwool
 - Composite Boards




Rigid Insulation Anchors

VJT Code	Description	Drill-Ø (mm)	Max. Fixture Thickness (mm)	Embed Depth (mm)	Min. Drill Depth (mm)	Overall Length (mm)	Box Qty
01800010	8 x 50 - 0/30 Rigid (61905)	8	0 - 20	30	40	50	500
01800020	8 x 70 - 30/40 Rigid (61905)	8	20 - 40	30	40	70	500
01800030	8 x 90 - 50/60 Rigid (61905)	8	50 - 60	30	40	90	500
01800040	8 x 110 - 70/80 Rigid (61905)	8	70 - 80	30	40	110	500
01800045	8 x 130 - 90/100 Rigid (61905)	8	90 - 100	30	40	130	500
01800060	90mm Insulation Washer	-	-	-	-	-	1000


Installation Procedure



1. Drill hole to correct diameter and recommended depth.



2. Insert the anchor into the drilled hole.



3. Hammer the anchor home until contact is made with the insulation.