Paslode Impulse IM200 / 50 S16 Gas Stapler

Gas Systems





Heavy Duty Cordless Stapler is used for medium to heavy duty stapling applications.



Eurocode & Description

- Eurocode: 900078 IM200 / 50 S16 Stapler
- **Box Qty**

Paslode: Direct Fixings

Technical Specification

Weight:	2.9kg	
Dimensions:	345 x 320 x 95mm	
Staple range:	16mm to 50mm	
Cycle rate:	2 staples per sec	
Max. cycle rate:	500 per hour	
	3,000 per day	
Magazine capacity:	150 staples	
Fuel cell life:	Approx. 1,000	
Battery:	Approx. 4,000	
	fixings per charge	
Charger 230 volt:	Maximum charge	
	time of 2 hours	

time of 2 nours

Substrates

- Wood
- Plasterboard

Applications

- Overboarding
- Packaging
- Fire protection with FP Conversion Kit 013015 (fireproofing plasterboard)



Kit Contains:

Paslode Impulse IM200 / 50 S16 Gas Stapler, high impact lightweight carry case, 2 x batteries, battery charger, cleaning solution, Impulse lubricant, safety glasses to EN166:F, allen key and instruction manual.

Product Advantages

- Cordless, self powered No hoses, no compressors, no setting up time
- Powerful Driving up to a maximum of 2 staples per second and 500 per hour
- Tough Constructed from heavy duty, reinforced durable housing, guaranteed for five years
- Lightweight Centrally balanced body with textured 'Sure Grip' handle
- Quick clear feature Allowing easy access to nose, reducing down time

Fastener Specification

Coatings / Materials / Finishes:	Galvanised
Staple Gauges:	F16 Wire size 1.65mm
Crown Width:	12.7mm
Point Types:	Divergent - Staple legs fasten in opposite directions to increase the strength of fix. Chisel - Reduces the risk of wood splitting. Staple legs remain parallel after application
Collation Types:	Glued

GALV

Stapler Consumables

Staple and Fuel Packs for IM200 / 50 S16 Furnende



Eurocode	Gauge	Length	Point / Finish
921367	GS16	16mm	DIV GALV
921368	GS16	19mm	CH GALV
921369	GS16	25mm	DIV GALV
921370	GS16	35mm	DIV GALV
921371	GS16	50mm	CH GALV

• Sequential actuation - Safe operation

.....

• Slim line - User friendly battery pack



Sequential Actuation (Nose piece attachment for FP Conversion Kit)



'Sure Grip' handle

Fuel Cells Box Otv

3

3

3

3

3

2,100

2,100

2,100

2,100

2,100