

Cladfix

For fixing profiled metal cladding into cold rolled steel.

This comprehensive range of high quality self drilling fasteners are designed to provide the industry with fixings that give very rapid

and accurate installation with precision drill points eliminating 'skip action' to prevent damage to the face of the profile.

APPLICATIONS

For fixing profile metal, Cladding single skin or insulation to cold rolled, Rails and purlins 1.2-5.3mm Thick.

HEAD STYLES

Hexagon head $\frac{5}{16}$ across flats certain sizes available with $\frac{3}{8}$ AF.

BENEFITS

- Super fast drill speed.
- Excellent pullout in thin materials.
- Extra thick deposit of zinc ensures resistance.

SPECIFICATIONS

Manufactured from carbon steel heat treated and zinc plated to 12 microns.

CFT27



6.3x160mm No 4pt

CFT26




5.5x98mm No 3pt

CFT25




5.5x82mm No 3pt

ASF38




5.5x70mm No 3pt

ASF23




5.5x57mm No 3pt

ASF21




5.5x51mm No 3pt

ASF3




5.5x50mm No 3pt

ASF12




5.5x43mm No 3pt

ASF2




5.5x38mm No 3pt

ASF15







5.5x32mm No 3pt

ASF17




5.5x25mm No 3pt

Fasteners shown are available pre-assembled				
Code	Dia	EPDM Thickness	Application	
	G12	12mm	2.1	Isolator
	G16	16mm	2.1	Side wall
	G19	19mm	3.0	Roof
	G29	29mm	3.0	Roof lights


For Fasteners assembled post fix product code with washer code ie ASF17/G16

ASF2271




5.5x25mm No 3pt Recommended for fixing Gridtite bracket to Purlins
Large Flange 6.3x22mm No 3

CFT11




4.8x20mm No 3pt

ASF414



6.3x25 14/3pt

ASF11



5.5x38mm No 3pt