



## DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type :

**Drywall Screws**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

**British Gypsum Drywall Screws, British Gypsum Collated Drywall Screws,  
British Gypsum Drywall Timber Screws, British Gypsum Collated Drywall Timber Screws,  
British Gypsum Jack-Point Screws, British Gypsum Wafer Head Screws,  
British Gypsum Wafer Head Jack-Point Screws, British Gypsum Rigidur Screws,  
British Gypsum Glasroc F FIRECASE Screws, British Gypsum GypFloor SIF5 Floor Screws**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

**Fasteners for gypsum based plasterboards**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

**British Gypsum  
Registered in England 734396  
East Leake, Loughborough, Leicestershire LE12 6HX  
Tel : +44 (0) 115 9451000**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN14566: 2008+A1: 2009**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**N/A**

9. Declared performance:

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Withdrawal force	450N	EN14566: 2008+A1: 2009
Reaction to fire	A1	EN14566: 2008+A1: 2009
Flexural strength	10°	EN14566: 2008+A1: 2009
Drilling performance test	1 secs for self tapping 4 secs for self drilling	EN14566: 2008+A1: 2009
Hardness	Case hardness HRC55 min depth 0.5mm	EN14566: 2008+A1: 2009

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Certified in accordance with:  
Environmental Management System ISO 14001:2004,  
Quality Management System ISO 9001:2008,  
Responsible Sourcing Standard BES 6001: 2009 (very good).

Signed for and on behalf of the manufacturer by:

Mike Chaldecott, Managing Director British Gypsum



Signature

28/6/13

Place and date of issue

EL

