



SAFETY DATA SHEET CEMENTONE FLEXACRYL GREY

According to Regulation (EC) No 1907/2006

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name CEMENTONE FLEXACRYL GREY
Product No. 17500, 17501, 17502, 17507, 175006, 17524, 17508x

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier BOSTIK LIMITED
COMMON ROAD
STAFFORD
STAFFORDSHIRE
ST16 3EH
+44 1785 272625
sds.uk@bostik.com

1.4. Emergency telephone number

+44 1785 272650 (24 Hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

| | | |
|-------------------------------|-------------------------------|---------------------|
| Classification (EC 1272/2008) | Physical and Chemical Hazards | Flam. Liq. 3 - H226 |
| | Human health | Not classified. |
| | Environment | Not classified. |

Classification (1999/45/EEC) R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



| | | |
|--------------------------|---|--|
| Signal Word | Warning | |
| Hazard Statements | H226 Flammable liquid and vapour. | |
| Precautionary Statements | P102 Keep out of reach of children. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+352 IF ON SKIN: Wash with plenty of soap and water. P403+235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local regulations. | |

CEMENTONE FLEXACRYL GREY

Supplementary Precautionary Statements

| | |
|----------|--|
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P370+378 | In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. |

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | | |
|--|---|---------------------------------------|
| 1-METHOXY-2-PROPANOL | | 5-10% |
| CAS-No.: 107-98-2 | EC No.: 203-539-1 | Registration Number: 01-2119457435-35 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H336 | Classification (67/548/EEC) R10 R67 | |
| 2-METHOXY-1-METHYLETHYL ACETATE | | 30-60% |
| CAS-No.: 108-65-6 | EC No.: 203-603-9 | Registration Number: 01-2119475791-29 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 | Classification (67/548/EEC) R10 | |
| 2-METHOXY-1-METHYLETHYL ACETATE | | < 1% |
| CAS-No.: 108-65-6 | EC No.: 203-603-9 | Registration Number: 01-2119475791-29 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Eye Irrit. 2 - H319 | Classification (67/548/EEC) Xi;R36. R10. | |
| XYLENE | | < 1% |
| CAS-No.: 1330-20-7 | EC No.: 215-535-7 | Registration Number: 01-2119488216-35 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 | Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

CEMENTONE FLEXACRYL GREY

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists after washing.

Eye contact

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

No specific symptoms noted.

Ingestion

No specific symptoms noted.

Skin contact

No specific symptoms noted.

Eye contact

No specific symptoms noted.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Generates massive smoke during fire. Vapours are heavier than air and may spread near ground to sources of ignition. HIGHLY FLAMMABLE! Risk of explosion in closed containers if pressure rises rapidly.

Specific hazards

Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Special Fire Fighting Procedures

Use water SPRAY only to cool containers! Do not put water on leaked material. Be aware of danger of explosion. Use supplied air respirator if product is involved in a fire. Avoid breathing fire vapours. Keep up-wind to avoid fumes. If possible, fight fire from protected position.

Protective equipment for fire-fighters

Wear self contained breathing apparatus

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment.

6.2. Environmental precautions

Prevent entry into drains and water courses.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb onto sand, earth or absorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

CEMENTONE FLEXACRYL GREY

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Ground container and transfer equipment to eliminate static electric sparks. Store at moderate temperatures in dry, well ventilated area.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|---------------------------------|-----|----------------|------------------|----------------|------------------|-------|
| 1-METHOXY-2-PROPANOL | WEL | 100 ppm(Sk) | 375 mg/m3(Sk) | 150 ppm(Sk) | 560 mg/m3(Sk) | |
| 2-METHOXY-1-METHYLETHYL ACETATE | WEL | 50 ppm(Sk) | 274 mg/m3(Sk) | 100 ppm(Sk) | 548 mg/m3(Sk) | |
| 2-METHOXY-1-METHYLETHYL ACETATE | WEL | 50 ppm(Sk) | 274 mg/m3(Sk) | 100 ppm(Sk) | 548 mg/m3(Sk) | |
| XYLENE | WEL | 50 ppm(Sk) | 220 mg/m3(Sk) | 100 ppm(Sk) | 441 mg/m3(Sk) | |

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures

Explosion-proof general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Resistant material. Nitrile.

Use thin cotton gloves inside the rubber gloves if allergy risk.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------|--------------------------|
| Appearance | Paste |
| Colour | Grey. |
| Odour | Slight odour of alcohol. |
| Relative density | 1.0 |
| Flash point (°C) | > 32 |
| Auto Ignition Temperature (°C) | ~270 |

CEMENTONE FLEXACRYL GREY

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available

10.2. Chemical stability

Avoid Heat, sparks, flames.

10.3. Possibility of hazardous reactions

Not available.

Hazardous Polymerisation

Unknown.

10.4. Conditions to avoid

Not known.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Fire or high temperatures create: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

Gas or vapour may irritate respiratory system.

Ingestion

Harmful: may cause lung damage if swallowed.

Skin contact

May cause skin irritation/eczema.

Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

Health Warnings

Defats the skin. Prolonged or repeated exposure may cause severe irritation.

Medical Considerations

Skin disorders and allergies.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided

12.1. Toxicity

12.2. Persistence and degradability

Degradability

No data available.

12.3. Bioaccumulative potential

CEMENTONE FLEXACRYL GREY

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Do not allow runoff to sewer, waterway or ground. Recover and reclaim or recycle, if practical. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

| | |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |

14.2. UN proper shipping name

Proper Shipping Name PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

| | |
|---------------------|-----------------------------|
| ADR/RID/ADN Class | 3 |
| ADR/RID/ADN Class | Class 3: Flammable liquids. |
| ADR Label No. | 3 |
| IMDG Class | 3 |
| ICAO Class/Division | 3 |
| Transport Labels | |



14.4. Packing group

| | |
|---------------------------|-----|
| ADR/RID/ADN Packing group | III |
| IMDG Packing group | III |
| ICAO Packing group | III |

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

EMS F-E, S-E

CEMENTONE FLEXACRYL GREY

Emergency Action Code •3YE
Hazard No. (ADR) 30
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

Issued By Approved LJ
Revision Date January 2014
Revision 10
Date December 2006

Risk Phrases In Full

R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R36 Irritating to eyes.
R38 Irritating to skin.
R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H312 Harmful in contact with skin.
H336 May cause drowsiness or dizziness.