

Revision Date January 2014

Revision 10



SAFETY DATA SHEET EVO-STIK GUNNABLE

According to Regulation (EC) No 1907/2006

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name EVO-STIK GUNNABLE
Product No. 292208, 292604

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier BOSTIK LIMITED
COMMON ROAD
STAFFORD
STAFFORDSHIRE
ST16 3EH
+44 1785 272625
sds.uk@bostik.com

1.4. Emergency telephone number

+44 1785 272650 (24 Hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	STOT SE 3 - H336
Environment	Aquatic Chronic 3 - H412

Classification (1999/45/EEC) F;R11. R52/53, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Environment

The primary environmentally hazardous substance in this formulation has been tested to Annex V of Directive 67/548/EEC by the supplier and has been reclassified as R51/53. This Product has therefore been reclassified to take into account the new information.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

EVO-STIK GUNNABLE

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing vapour/spray.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements	
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P273	Avoid release to the environment.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

2.3. Other hazards

Vapours are heavier than air and can travel long distances to a source of ignition Pilot lights can ignite the vapour Vapours may cause drowsiness and dizziness

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

CYCLOHEXANE		< 1%
CAS-No.: 110-82-7	EC No.: 203-806-2	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 2 - H225	F;R11	
Skin Irrit. 2 - H315	Xn;R65	
STOT SE 3 - H336	Xi;R38	
Asp. Tox. 1 - H304	R67	
Aquatic Acute 1 - H400	N;R50/53	
Aquatic Chronic 1 - H410		
NAPHTHA (PETROLEUM), HYDRODESULFURIZED LIGHT, DEAROMATIZED; <0.1% BENZENE		10-30%
CAS-No.: 92045-53-9	EC No.: 295-434-2	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 2 - H225	Xn;R65.	
Skin Irrit. 2 - H315	Xi;R38.	
STOT SE 3 - H336	F;R11.	
Asp. Tox. 1 - H304	N;R51/53.	
Aquatic Chronic 2 - H411	R67.	

EVO-STIK GUNNABLE

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, <0.1% BENZENE,		5-10%
CAS-No.: 64742-49-0	EC No.:	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
N-HEXANE		< 1%
CAS-No.: 110-54-3	EC No.: 203-777-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) F;R11 Repr. Cat. 3;R62 Xn;R65,R48/20 Xi;R38 R67 N;R51/53	
PROPAN-2-OL		< 1%
CAS-No.: 67-63-0	EC No.: 200-661-7	Registration Number: 01-2119457558-25
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R67	
QUARTZ		< 1%
CAS-No.: 14808-60-7	EC No.: 238-878-4	
Classification (EC 1272/2008) STOT RE 2 - H373	Classification (67/548/EEC) Xn;R48/20.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately!

Skin contact

Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

EVO-STIK GUNNABLE

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Water spray, fog or mist. Foam. Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

May explode when heated or when exposed to flames or sparks. May travel considerable distance to source of ignition and flash back. Vapour explosion and poison hazard indoors, outdoors and in sewers.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep run-off water out of sewers and water sources. Dike for water control. Cool containers exposed to flames with water until well after the fire is out. Move container from fire area if it can be done without risk. Use water spray to reduce vapours. If risk of water pollution occurs, notify appropriate authorities.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Runoff or release to sewer, waterway or ground is forbidden. Absorb in vermiculite, dry sand or earth and place into containers. Do not let washing down water contaminate ponds or waterways. Collect in containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Provide good ventilation. Avoid spilling, skin and eye contact. Avoid acids, moisture, and combustible materials.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Isolate from other materials. Store in tightly closed original container in a dry, cool and well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

EVO-STIK GUNNABLE

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
CYCLOHEXANE	WEL	100 ppm	350 mg/m ³	300 ppm	1050 mg/m ³	
N-HEXANE	WEL	20 ppm	72 mg/m ³			
PROPAN-2-OL	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³	
QUARTZ			0.1 mg/m ³			

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate general and local exhaust ventilation. Explosion-proof general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Nitrile.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Provide eyewash station. Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Yellowish
Odour	of solvents
Flash point (°C)	-25

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

EVO-STIK GUNNABLE

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system.

Ingestion

Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

Liquid may irritate skin.

Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

Medical Considerations

Chronic respiratory and obstructive airway diseases. Skin disorders and allergies. History of smoking.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains a substance which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

No data available

12.2. Persistence and degradability

Degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

Semi-mobile.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN)

1133

EVO-STIK GUNNABLE

UN No. (IMDG) 1133
UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper Shipping Name ADHESIVES

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3
ADR/RID/ADN Class Class 3: Flammable liquids.
ADR Label No. 3
IMDG Class 3
ICAO Class/Division 3
Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS F-E, S-D
Emergency Action Code •3YE
Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EVO-STIK GUNNABLE

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

Issued By	Approved LJ
Revision Date	January 2014
Revision	10
Date	August 2006

Risk Phrases In Full

R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R38	Irritating to skin.
R62	Possible risk of impaired fertility.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.