

Restraint Straps

Horizontal and vertical straps designed to building regulation B55268 Part 3 and other building standards fixing to masonry walls when connecting timber floor and roof systems to the main structure.

These items also available as Timber Frame Cavity Straps.

LDMH - Galvanised

SLDMH - Stainless Steel

30mm x 2.5mm multi-holed straps supplied in 100mm increments.

6mm holes at 25mm offset centres.

Available straight, bent or twisted or in combinations as required in both galvanised (LDMH) and stainless steel (SLDMH).

Fixing

Fix using either no.12 x 50mm BZP wood screws or 75mm x 4.0mm galvanised nails - for stainless straps stainless fixings must be used.

Packed in bundles of 20.



HDMH - Galvanised

SHDMH - Stainless Steel

30mm x 5.0mm multi-holed straps supplied in 100mm increments.

6mm holes at 25mm offset centres.

Available straight, bent or twisted or in combinations as required in both galvanised (HDMH) and stainless steel (SHDMH).

Fixing

Fix using either no. 12 x 50mm BZP wood screws or 75mm x 4.0mm galvanised nails - for stainless straps stainless fixings must be used.

Packed in bundles of 10.



Ordering

When ordering straps please quote the overall girth from end to end of the strap including any bends or twists or both ie 1200mm x 30mm x 5.0mm bent at 100mm = a strap 1100mm long leg plus a 100mm bend. When ordering straps that are both bent and twisted ensure that you specify the distance of the twist from the bend.