

## DECLARATION OF PERFORMANCE

**Factory Control Certificate Number: 0013-CPD-537588**

**1. Product Group:**

Type A – Pitch / Bitumen DPC Sheets

**2. Unique Product Names / Codes**

Product name	Unique Identification Code	Nominal dimensions
Hyload Original	31599900	20m x various widths
Hyload Housebuilder	36599900	20m x various widths
Damp-Protac	31199900	20m x various widths
Permabit	34599900	20m x various widths

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Linear damp proof course (DPC), bonded at joints.

**4. Manufacturer:**

IKO PLC  
Appley Lane North  
Appley Bridge  
Wigan  
Lancashire  
WN6 9AB

**5. Authorised Representative:**

Not Applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:**

2+

**7. Harmonised standard:**

EN 13969:2004

**8. Notified Body:**

BSi

**9. Declared Performance:**

Essential Characteristic	Performance	Harmonised Technical Specification
Watertightness	2kPa for 24 hrs	EN 1928
Maximum tensile force	≥ 3 Mpa	EN 12311-1
Elongation	≥ 110%	EN 12311-1
Resistance to static loading	20kg (Concrete) 5kg (EPS)	EN 12730 (B)

Resistance to impact	500mm (Aluminium) 150 (EPS)	EN 12691
Resistance to tearing	Long $\geq$ 8.63N/mm	EN 12310-1
Flexibility at low temperature	$\geq$ -15	EN 1109

Signed for and on behalf of the manufacturer by:



Terry Edwards  
R&D and Quality Manager  
Wigan, July 2013

---