

Declaration of Performance

ANCON hereby declares that the product range identified as,

Staifix STF6 50mm

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as an,

Asymmetrical Wall Tie covered in clause 1 of the standard

Intended Use:

Type 6 wall tie for connecting a masonry outer leaf to a structural timber frame. Suitable for 50mm cavities.

Notified Body:	CERAM Research Limited
	Queens Road, Penkhull
	STOKE-ON-TRENT ST4 7LQ
	United Kingdom
	Tel: +44 (0)1782 764444
Notified Body Number:	1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity:	483N
Tensile Load Capacity:	657N
Water Shedding Capability:	Resistant
Durability:	Material/coating reference 3, Steel grade 1.4301
Dangerous Substances:	None
Conditions	
Embedment Depth:	77mm

Type M2 (iv)

timber frame

up to 24mm max. to accommodate shrinkage of

Refer to Table B.1. BS 5268-6.1:1996

10mm

Manufactured by:



Ancon Building Products President Way President Park Sheffield S4 7UR United Kingdom

Tel: +44 (0)114 275 5224 Fax: +44 (0)114 276 8543 Email: info@ancon.co.uk Web: www.ancon.co.uk Twitter: @AnconUK

Same

Minimum Mortar Class:

Movement Tolerance:

Recommended Spacing:

Authorised by:

Minimum Mortar Joint Width:

Stuart Maxwell, Managing Director, on 16th May 2013