

Declaration Number: A0052-00-EN

Declaration of Performance

ANCON hereby declares that the product range identified as,

Staifix STF6 100mm

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as an,

Asymmetrical Wall Tie covered in clause 1 of the standard

Intended Use: Type 6 wall tie for connecting a masonry outer leaf

to a structural timber frame. Suitable for 100mm

cavities.

Notified Body: CERAM Research Limited

Queens Road, Penkhull STOKE-ON-TRENT ST4 7LQ

United Kingdom

Tel: +44 (0)1782 764444

Notified Body Number: 1289

This product conforms to **System 3 -** Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity: **540N**Tensile Load Capacity: **660N**

Water Shedding Capability: Resistant

Durability: Material/coating reference 3, Steel grade 1.4301

Dangerous Substances: None

Conditions

Embedment Depth: 77mm

Minimum Mortar Class: Type M2 (iv)

Minimum Mortar Joint Width: 10mm

Movement Tolerance: up to 24mm max. to accommodate shrinkage of

timber frame

Recommended Spacing: Refer to Table B.1. BS 5268-6.1:1996

Authorised by:

Marce Q

Stuart Maxwell, Managing Director, on 16th May 2013

Manufactured by:

Ancon BUILDING PRODUCTS

Ancon Building Products
President Way

President Way
President Park
Sheffield S4 7UR
United Kingdom

Tel: +44 (0)114 275 5224 Fax: +44 (0)114 276 8543 Email: info@ancon.co.uk Web: www.ancon.co.uk Twitter: @AnconUK