
Sinops Limited





DATA SHEET

Scaffold Screw Eyes

We confirm our range of Scaffold Screw Eyes are manufactured from Grade 4.8 Mild Steel with a BZP finish.

Performance Testing

Ultimate Tensile Strength (Maximum Loading of Threaded part in kN) testing has been performed by Zhejiang Guo Jian Testing Technology Co. Limited with the following results:-

Test Item	Test Method	Requirement	Test Result	Conclusion	Test Date	Certificate No.
M12 x160mm	GB/T 228.1-2010	n/a	43.14kN *	n/a	30/12/2016	201631716
M12 x 230mm	GB/T 228.1-2010	n/a	46.04kN *	n/a	30/12/2016	201631717

^{* -} Fracture first appears in thread at this load

Range

Code	Shaft Diameter	Shaft Length	Max'm Usable Length	Thread Length	Eye Diameter	Box Qty
02500010	12mm	90mm	15mm	65mm	23mm	25pcs
02500020	12mm	120mm	45mm	65mm	23mm	25pcs
02500030	12mm	160mm	85mm	65mm	23mm	25pcs
02500040	12mm	190mm	115mm	65mm	23mm	25pcs
02500050	12mm	230mm	155mm	65mm	23mm	25pcs
02500060	12mm	300mm	225mm	65mm	23mm	25pcs
02500070	12mm	350mm	275mm	65mm	23mm	25pcs

Applications & Design Features

Used for tying in scaffolding structures, for securing into concrete, solid brick, hollow brick, concrete blocks and natural stone.

High load bearing capacity with a high quality weld on the eye to prevent the eye from bending. Screw-in markings on the shaft to guarantee screw-depth and prevent the eye from being unintentionally broken off.

Installation Requirements

For use with a nylon Scaffold Plug (14 x 70mm or 14 x 100mm)

This declaration of conformity is valid until there is significant change in the product and characteristics.

Signed By:

Richard Dunn

Position:

Managing Director

Date:

Name:

31 January 2017

This delaration is the responsibility of the importer

Sinops Limited, 5-B, Redlake, Road, Pedmore, Stourbridge, West Midlands DY9 ORU