



Material	Carbon steel, C15
Safety Factor	MBL equals 6 x WLL
Standard	Generally to DIN580
Finish	Self colour or electro galvanised
Certification	As standard; EC Declaration of Conformity Upon request; 2.2, 2.1, CE

WLL	Diameter Thread	Diameter Base	Diameter Eye		Length	Thickness Base	Height	Product Code		Weight Each
			Outside	Inside				Self Colour	Zinc Plated	
t	a	b	c	d	e	f	g			kg
	mm	mm	mm	mm	mm	mm	mm			
0.07	6	20	36	20	13	6	36	25001	25501	0.06
0.14	8	20	36	20	13	6	36	25002	25502	0.06
0.23	10	25	45	25	17	8	45	25003	25503	0.10
0.34	12	30	54	30	20.5	10	53	25004	25504	0.18
0.49	14	35	63	35	27	12	60	25005	25505	0.28
0.7	16	35	63	35	27	12	62	25006	25506	0.28
0.9	18	40	72	40	30	14	71	25007	25507	0.41
1.2	20	40	72	40	30	14	71	25008	25508	0.42
1.5	22	45	81	45	35	14	80	25009	25509	0.67
1.8	24	50	90	50	36	18	90	25010	25510	0.83
2.5	27	50	90	50	36	18	90	25011	25511	1.22
3.2	30	65	108	60	45	22	109	25012	25512	1.66
4.3	33	65	108	60	45	22	110	25013	25513	2.16
4.6	36	75	126	70	54	26	128	25014	25514	2.65
6.1	39	75	126	70	54	26	130	25015	25515	3.34
6.3	42	85	144	80	63	30	147	25016	25516	4.03
8	45	85	144	80	63	35	150	25017	25517	5.25
8.6	48	100	166	90	68	35	168	25018	25518	6.32
11.5	56	110	184	100	78	38	187	25019	25519	8.80
16	64	120	206	110	90	42	208	25020	25520	12.40
21	72	150	260	140	100	50	260			22.93
28	80	170	296	160	112	55	298			32.00
40	100	190	330	180	130	60	330			48.00