



<b>Material</b>	Carbon steel, C15
<b>Safety Factor</b>	MBL equals 6 x WLL
<b>Standard</b>	Generally to DIN582
<b>Finish</b>	Self colour or electro galvanised
<b>Certification</b>	As standard; EC Declaration of Conformity Upon request; 2.2, 2.1, CE

WLL	Diameter Thread	Diameter Base	Diameter		Thickness Base	Height	Product		Weight Each
			Outside	Inside			Code	Code	
t	a	b	c	d	e	f	Self Colour	Zinc Plated	kg
	mm	mm	mm	mm	mm	mm			
0.07	6	20	36	20	8.5	36	26001	26501	0.05
0.14	8	20	36	20	8.5	36	26002	26502	0.05
0.23	10	25	45	25	10	45	26003	26503	0.09
0.34	12	30	54	30	11	53	26004	26504	0.16
0.49	14	35	63	35	13	60	26005	26505	0.22
0.7	16	35	63	35	13	62	26006	26506	0.24
0.9	18	40	72	40	16	71			0.36
1.2	20	40	72	40	16	71	26007	26507	0.35
1.5	22	45	81	45	18	80	26008	26508	0.59
1.8	24	50	90	50	20	90	26009	26509	0.71
2.5	27	50	90	50	20	90	26010	26510	1.02
3.2	30	65	108	60	25	109	26011	26511	1.32
4.3	33	65	108	60	25	110	26012	26512	1.70
4.6	36	75	126	70	30	128	26013	26513	2.08
6.1	39	75	126	70	30	130	26014	26514	2.60
6.3	42	85	144	80	35	147	26015	26515	3.11
8	45	85	144	80	35	150	26016	26516	4.07
8.6	48	100	166	90	40	168	26017	26517	5.02
8.6	52	110	184	100	45	187			8.30
11.5	56	110	184	100	45	187			6.69
16	64	120	206	110	50	208			9.30
21	72	150	260	140	60	260			15.00