



Dry



Wet



Heat



Oily



Cold



Chemical



TG165

A lightweight, rubber coated handling glove with Level 4 tear resistance for rugged handling tasks in wet and dry conditions.

Key Features

- Rugged and durable grip
- High tear resistance
- Good dexterity
- Flexible

Ideal for

- Groundwork
- Construction (trades)
- Transport
- Highways maintenance
- Goods handling & warehousing

Sizes:	6-11	Gauge:	10gg
Liner:	Polycotton	Coating:	X-Dura Latex
No/Bag:	10	No/Carton:	200

TG165

Glove Specifications

Glove lengths

210mm-250mm

Glove Weight

10 gauge

Liner Type

Polycotton

Glove colour

Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour

Black

Dip type

Latex

Dip Application

Palm Dipped

Glove Treatment

X-Dura



Packaging Information

Qty/bag

10 pairs

Qty/carton

200 pairs

Carton Dimensions

300mm x 600mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.