

Window Protection Film (Blue)

Technical Datasheet



VJ Technology Limited
Technology House, Brunswick Road,
Cobbs Wood Industrial Estate,
Ashford, Kent. TN23 1EN
t. 01233 637695
e. enquiries@vjtechnology.com
www.vjtechnology.com

Description & Application

Transparent and weather stable polyester film with a scratch resistant surface and a strong acrylic adhesive.

Advantages

This tape features:

- Good weathering resistance
- Significant reduction in the transmission of UVA and UVB rays
- High tensile strength and elongation at break increases resistance of the glazing system to impact and pressure

Technical Performance	Data
Tape Thickness (u)*	40 (+/-) 0.005)
Tape Width (mm)	100
Tape Length Variance (m)	+/- 0.5
Tensile Strength (N/25mm)**	48
Adhesion (N/25mm)***	70g

*Thickness to test standard GF7125-1999

**Tensile Strength to test standard GB7753-1987

***Adhesion to test standard GB/T72792-1998

This data sheet is valid until there is significant change in the product and characteristics.

All product specifications and data are subject to change without notice. The data contained in this datasheet is believed to be accurate and is reproduced in good faith, it is the customers responsibility to ensure that the product described in the datasheet is suitable for their application.

This product is supplied by Sinops - part of the VJ Technology Group. Sinops disclaim any and all liability for any errors, inaccuracies or incompleteness contained in the datasheet. In addition Sinops and VJ Technology make no warranty, representation or guarantee regarding the suitability of the product described by the datasheet for any particular or associated purchase.