

Knauf Performance Plus Screws Collated/Non Collated

Data Sheet

Knauf Performance Plus Screws are designed for single and double layer Knauf Performance/Soundshield Plus partition systems.

Knauf Application

Knauf Performance Plus Screws provide a solid fix into plasterboards with a dense consistency. Should be used in conjunction with Knauf Performance Plus, Knauf Impact Panel and Knauf Soundshield Plus.

High density board to steel, 0.55 - 1 mm (Approx.)

Physical Characteristics



Non-collated

Dimensions (mm)		Material No	Pack Details	
Length	Diameter		Items per Pack	Kg (Approx.)
25	3.9	404662	1000	1.9
35	3.9	404663	1000	2.3
45	3.9	404664	1000	2.7

Collated

Dimensions (mm)		Material No	Pack Details	
Length	Diameter		Items per Pack	Kg (Approx.)
25	3.9	525676	1000	1.9
35	3.9	525680	1000	2.3
45	3.9	525682	1000	2.7

Compliance

EN 14566

Performance Data

Fire performance

A1 Non-combustable




Product Specification

Gauge 3.9mm (Approx.)

Head Type Flat Head

Recess Type 6.75mm (Approx.) Phillips

Thread Type Single lead with reverse thread near head



Product Features

Supplied in packs of 1000 screws.

Collated material packs contain strips of 50 screws. These are suitable for a wide range of auto feed screw guns.

Collated material packs supplied with one high performance Ph2 bit.

Reversed thread design to pull board tight.


Flat head to facilitate seating and minimize strip out.

Finish - Phosphate.

Application/Installation

Guidelines

Use a standard screw gun with a depth-sensitive nose piece. Suggested screw gun specification for optimal performance - 4amps minimum and 2500 RPM.



Install with head flush with board, no need to counter sink. Over driving may result in failure of the fastener or stripout of the work surface.

Health & Safety

Refer to the product MSDS and also the Knauf guidance for Safe Material Management document.

MSDS: <http://www.knauf.co.uk/product-data-sheets>

Safe Material Management: <http://www.knauf.co.uk/literature>

Website

www.knauf.co.uk

Customer Service

Tel: 0800 521 050

Fax: 0800 521 205

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

