Commercial Product Name: Fire Stop Gun Foam

Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name Fire Stop Gun Foam

Unique Formulation Identifier

VV30-X0TX-U00V-KQN8

(UFI)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses One-component polyurethanic foam

Observe technical data sheet.

Recommended restrictions None under normal processing.

1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer Great Britain: Mrs Mirka Valovicova, fischer Fixing (UK) Ltd

Hithercroft Road

Wallingford, Oxfordshire, OX10 9AT Telephone: +44 01491 827 920

FAX: +44 01491 827 950 Internet: www.fischer.co.uk

1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

tion (EC) No. 1272/2008

Classification according to Regula- Aerosol 1; H222 H229 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3;

H335 STOT RE 2; H373

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en

2.2 Label elements

Hazard pictogram







Signal word Danger

Hazardous component(s) to be in-

dicated on label

Diphenylmethanediisocyanate, isomers and homologues

H-statement(s) H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated ex-

posure.

P101: If medical advice is needed, have product container or label at P-statement(s)

hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray. P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face pro-

tection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

P410+P412: Protect from sunlight. Do no expose to temperatures ex-

ceeding 50 °C/122 °F.

P501: Dispose of contents/container to special waste treatment.

Further information Pressurized container: protect from sunlight and do not expose to tem-

> peratures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Buildup of explosive mixtures possible without sufficient ventilation.

> > 2/17

Commercial Product Name: Fire Stop Gun Foam

fischer ***

Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

EUH204: Contains isocyanates. May produce an allergic reaction.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 accord-

ing to standard EN 14387) is used.

2.3 Other hazards

Health hazard No information available.

Particular information pertaining specific risk for human / environ-

No information available.

ment

Indication of danger No information available.
Hazard precautions No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
Diphenylmethanediiso- cyanate, isomers and ho- mologues	CAS No.: 9016-87-9 EC-No.: 618-498-9 REACH No.: The substance does not require registra- tion according to Regulation (EC) No 1907/2006 [REACH].	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	30.0 - 60.0 % by weight
Phosphorous oxychloride, reaction products with propylene oxide	CAS No.: 1244733-77-4 EC-No.: 911-815-4 REACH No.: 01-2119486772-26	Acute Tox. 4; H302	< 25.0 % by weight
Halogenated polyether- polyol	CAS No.: 86675-46-9	Acute Tox. 4; H302	< 15.0 % by weight
propane	CAS No.: 74-98-6 EC-No.: 200-827-9 Index-No.: 601-003-00-5 REACH No.: 01-2119486944-21	Flam. Gas 1; H220 Press. Gas; H280	< 15.0 % by weight
butane	CAS No.: 106-97-8 EC-No.: 203-448-7 Index-No.: 601-004-00-0 REACH No.: 01-2119474691-32	Flam. Gas 1; H220 Press. Gas; H280	< 15.0 % by weight
isobutane	CAS No.: 75-28-5 EC-No.: 200-857-2 Index-No.: 601-004-00-0 REACH No.: 01-2119485395-27	Flam. Gas 1; H220 Press. Gas; H280	< 15.0 % by weight
dimethyl ether	CAS No.: 115-10-6 EC-No.: 204-065-8 Index-No.: 603-019-00-8	Flam. Gas 1; H220 Press. Gas; H280	< 10.0 % by weight

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
	REACH No.:		
	01-2119472128-37,		
	01-2119519269-33		

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Take off immediately all contaminated clothing.

In case of accident or unwellness, seek medical advice immediately (show

directions for use or safety data sheet if possible).

Wear personal protection equipment (refer to section 8).

If inhaled Provide fresh air.

In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

Do NOT use solvents or thinners.

In case of eye contact Remove contact lenses.

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmol-

ogist.

If accidentally swallowed rinse the mouth with plenty of water (only if the

person is conscious) and obtain immediate medical attention.

Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention If unconscious place in recovery position and seek medical advice.

Special medical treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media spray mist, (water), Water spray jet, alcohol resistant foam, carbon diox-

ide, Extinguishing powder

Extinguishing media which must

t Full water jet

not be used for safety reasons

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising

Heating or fire can release toxic gas.

from the substance or prepara-

Pressurised container: May burst if heated.

Fight fire with normal precautions from a reasonable distance.

Commercial Product Name: Fire Stop Gun Foam

fischer Fischer

Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

tion itself, its combustion prod-

ucts, or released gases

5.3 Advice for firefighters

Special protective equipment for

firefighting

In case of fire: Wear self-contained breathing apparatus.

For the protection against direct skin contact, body protective clothing is

essential (in addition to the usual working clothes).

Additional information on fire-

fighting

Suppress (knock down) gases/vapours/mists with a water spray jet.

Keep containers and surroundings cool with water spray.

Do not allow water used to extinguish fire to enter drains, ground or wa-

terways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions For non-emergency personnel

Accidental release measures:

Wear personal protection equipment (refer to section 8).

Remove all sources of ignition.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water courses or the

soil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Allow stiffening. Take up mechanically.

Treat the recovered material as prescribed in the section on waste dis-

posal.

6.4 Reference to other sections

Reference to other sections Reference to other sections: 7 / 8 / 13

<u>SECTION 7: Handling and storage</u>

7.1 Precautions for safe handling

Advice on safe handling Vapours are heavier than air and may spread along floors. BEWARE:

Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

Do not spray on flames or red-hot objects.

Keep container tightly closed.

Hygiene measures: When using do not eat, drink or smoke. Wash hands

before breaks and after work.

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Take off contaminated clothing and wash it before reuse.

Precautions Handle and open container with care.

Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire

No special measures are necessary.

and explosion

Take measures to prevent the build up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Container may rupture on heating.
Keep/Store only in original container.
Keep container tightly closed and dry.
Store in accordance with local regulations.

Unsuitable materials for contain-

ers

Keep only in original container.

Hints on storage assembly Keep away from food, drink and animal feedingstuffs.

German storage class LGK 2B (TRGS 510)

Recommended storage tempera-

ture

+5 - 25 °C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

butane

Great Britain					
Long-term expo- sure value/ ppm	Long-term expo- sure value/ mg/ m3	Short-term expo- sure value / ppm	Short-term expo- sure value / mg/ m3	Note	Source
600	1450	750	1810	Carc; only applies if Butane contains more than 0.1% of buta-1,3-diene	EH40/2005 Work- place exposure limits (2011)

dimethyl ether

Great Britain				
Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3	
400	766	500	958	EH40/2005 Workplace
				exposure limits (2011)

Europe			
Long-term exposure value/	Long-term exposure value/	Issuing date	Source
mg/m3	ppm		
1 920	1 000	2000/39	DIRECTIVE 2009/161/EU

8.2 Exposure controls

Respiratory protection short-term (acute): AX

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Higher exposure: Self-contained respirator (breathing apparatus) (DIN EN

133)

Remarks Observe the wear time limits according GefStoffV in combination with the

rules for using respiratory protection apparatus (BGR 190).

Hand protection In case of contact through splashing:

Suitable material attached disposable gloves

Remarks Use gloves once only.

Note The attached gloves are intended as protection against short-term use.

•

In case of full contact:

Suitable material Protective gloves complying with EN 374. Butyl caoutchouc (butyl rubber),

NBR (Nitrile rubber), Fluorinated rubber, CR (polychloroprene, chloro-

prene rubber)

Unsuitable material PVC or rubber gloves are not recommended.

Material thickness >= 0,5 mm (adjust to application and duration of use)

Break through time >120 min

Remarks Replace when worn.

Note Request information on glove permeation properties from the glove sup-

plier.. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g.

temperature).

Eye protection Wear closely fitting protective glasses in case of splashes.

Safety glasses with side-shields conforming to EN166

Skin and body protection Long sleeved clothing

Note Choose body protection according to the amount and concentration of

the dangerous substance at the work place.

General protective and hygiene

measures

Do not eat, drink or smoke when using this product.

Avoid contact with the skin and the eyes.

Wash hands and face before breaks and after work and take a shower if

necessary.

Keep away from food, drink and animal feedingstuffs. Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental measures are necessary.

see section 6/7

Engineering measures Provide adequate ventilation.

Commercial Product Name: Fire Stop Gun Foam

Revision date: 10.12.2020





SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form aerosol

Colour various - see label

Odour characteristic

Odour threshold not determined

Melting point [°C] / Freezing point N

[°C]

No data available

Boiling point [°C] No data available

Flash point [°C] < 0 (Propellant)

Evaporation rate [kg/(s*m²)] No data available

Flammability (solid, gas) No data available

Explosion limits [Vol-%]

Lower limit 1,5 %

Upper limit 11 %

Vapour pressure [kPa] > 500

Vapour density No data available

Density [g/cm³] 1.3

Relative density No data available

Solubility No data available

Water solubility [g/l] insoluble

Solubility [g/l] No data available

Partition coefficient n-octanol /wa-

ter (log P O/W)

No data available

Autoinflammability not auto-flammable

Decomposition temperature [°C] No data available

Explosive properties not explosive.

Oxidising properties No

SECTION 10: Stability and reactivity

10.1 Reactivity

Reactivity No hazardous reaction when handled and stored according to provisions.

No decomposition if stored and applied as directed.

Commercial Product Name: Fire Stop Gun Foam

fischer Fischer

Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

10.2 Chemical stability

Chemical stability Stable when applying the recommended regulations for storage and han-

dling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Hazardous reactions No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Conditions to avoid The mixture is chemically stable under recommended conditions of stor-

age, use and temperature.

Direct sources of heat. Risk of bursting.

10.5 Incompatible materials

Materials to avoid Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition prod- No known hazardous decomposition products.

ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues			
Value Test criterion Test species Source			
> 10000	LD50	Rat	Company data

propane	
Value	Source
No data available	Company data

butane	
Value	Source
No data available	Company data

isobutane	
Value	Source
No data available	Company data

Dermal toxicity [mg/kg]

Diphenylmethar	iediisocyanate, isomei	rs and homologues		
Value	Test criterion	Test species	Remarks	Source
> 9400	LD50	Rabbit	OECD 402	Company data

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en

propane	
Value	Source
No data available	Company data

butane		
Value	Source	
No data available	Company data	

isobutane	
Value	Source
No data available	Company data

Inhalative toxicity [mg/l] Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues						
Value	Test criterion	Note	Exposure dura- tion	Source		
0,49 LC50 OECD 403 4 h Company data						

propane				
Value	Test criterion	Test species	Exposure dura- tion	Source
20	LC50	rat	4 h	Company data

butane				
Value	Test criterion	Test species	Exposure dura- tion	Source
658	LC50	rat	4 h	Company data

isobutane				
Value	Test criterion	Test species	Exposure dura- tion	Source
> 50	LC50	rat	4 h	Company data

dimethyl ether				
Value	Test criterion	Test species	Exposure dura- tion	Source
308	LC50	rat	4 h	Company data

Irritant effect on skin

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues			
Value Source			
Irritant	Company data		

Irritant effect on eyes **Hazardous ingredients**

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en

Diphenylmethanediisocyanate, isomers and homologues		
Value Source		
irritating Company data		

Irritant effect on the respiratory tract Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues		
Value Source		
Irritant Company data		

Sensitization

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues			
Value	Exposure type	Source	
sensitising		Company data	
sensitising	Inhalation	Company data	

Carcinogenic effects

Hazardous ingredients

Diphenylmet	Diphenylmethanediisocyanate, isomers and homologues				
Value	Measuring method	Test species	Dosage amount	Route of ex- posure	Source
Limited ev- idence of a carcinogenic effect.	OECD 453	Rat	1 mg/m³	inhalative	Company da- ta

Mutagenicity

Hazardous ingredients

nazaraous ingreateries	idzai dods ingredienes			
Diphenylmethanediisocyanate, isomers and homologues				
Value	Source			
Tests on bacterial or mammalian cell cultures did	Company data			
not show mutagenic effects.				

Reproduction toxicity

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues	
Value Source	
No toxicity to reproduction	Company data

Specific target organ toxicity (single exposure) [mg/kg]

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues				
Route of exposure	Specific effects	Organs affected	Source	
Inhalation	May cause respiratory irritation.	Respiratory system	Company data	

Specific target organ toxicity (repeated exposure) [mg/kg]

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues				
Route of exposure	Organs affected	Specific effects	Source	
inhalation	Respiratory system	May cause damage to organs through pro- longed or repeated exposure.	Company data	

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

Hazardous ingredients

Diphenylmet	Diphenylmethanediisocyanate, isomers and homologues				
Value	Test criteri- on	Test species	Measuring method	Exposure duration	Source
> 1000	LC50	Brachydanio rerio (ze- bra-fish)	OECD Test Guideline 203	96 h	Company da- ta

propane			
Value	Test criterion	Exposure duration	Source
> 1000	LC50	96 h	Company data

butane	
Value	Source
No data available	Company data

isobutane	
Value	Source
27,98	Company data

dimethyl ether	
Value	Source
> 1000	Company data

Toxicity to daphnia [mg/l]

Diphenylmet	Diphenylmethanediisocyanate, isomers and homologues				
Value	Test criteri- on	Test species	Exposure duration	Measuring method	Source
> 1000	EC50	Daphnia magna (Wa- ter flea)	24 h	OECD Test Guideline 202	Company da- ta

propane				
Value	Test criterion	Test species	Exposure dura- tion	Source

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en

14,22	LC50	Daphnia magna	48 h	Company data
		(Big water flea)		

butane	
Value	Source
No data available	Company data

isobutane	
Value	Source
14,22	Company data

dimethyl ether	
Value	Source
> 4400	Company data

Toxicity to algae [mg/l]

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues				
Value	Test criterion	Test species	Exposure dura- tion	Source
> 1640	ErC50:	Scenedesmus subspicatus	72 h	Company data

propane				
Value	Test criterion	Test species	Exposure dura- tion	Source
7,71	EC50	Scenedesmus quadricauda (Green algae)	96 h	Company data

butane	
Value	Source
No data available	Company data

isobutane	
Value	Source
7,71	Company data

dimethyl ether	
Value	Source
154,917	Company data

NOEC (daphnia) [mg/l]

Diphenylmethanediisocyanate, isomers and homologues				
Value	Test species	Measuring method	Exposure dura- tion	Source
> 10	Daphnia magna (Big water flea)	OECD 202	21 d	Company data

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

12.2 Persistence and degradability

Biodegradability

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues		
Value Source		
Not readily biodegradable.	Company data	

12.3 Bioaccumulative potential

Bioaccumulation

Hazardous ingredients

114241 4045 11161 64161165		
Diphenylmethanediisocyanate, isomers and homologues		
Value Source		
Bioaccumulation is unlikely.	Company data	

12.4 Mobility in soil

Mobility

Hazardous ingredients

Diphenylmethanediisocyanate, isomers and homologues		
Mobility Source		
No data available	Company data	

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination

Hazardous ingredients

nazar dods ingredients		
Diphenylmethanediisocyanate, isomers and homologues		
Value	Source	
This substance does not meet the PBT/vPvB criteria	Company data	
of REACH, Annex XIII.		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations Do not allow to enter into surface water or drains.

Dispose of waste according to applicable legislation.

Empty remaining contents.

Empty packaging: Where possible recycling is preferred to disposal or in-

cineration.

Product: Can be disposed of as a solid waste or burned in a suitable in-

stallation subject to local regulations.

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Print date: 10.12.2020 Version: 3.0/en

Waste Code According to the European Waste Catalogue, Waste Codes are not prod-

uct specific, but application specific.

The following Waste Codes are only suggestions:

Product

080501 - waste isocyanates

cured material

200000 - MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING

SEPARATELY COLLECTED FRACTIONS

160504 - gases in pressure containers (including halons) containing dan-

gerous substances

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1950	1950	1950
14.2 Description of the	AEROSOLS	AEROSOLS	Aerosols, flammable
goods			
14.3 Transport hazard	2	2.1	2.1
class(es)			
Remarks	flammable	(maximum 1 L) flammable	
Labels	2.1	2.1	2.1
Category	2		
Classification Code	5F		
Tunnel restriction code	D		
UN proper shipping name		AEROSOLS	Aerosols, flammable
EmS		F-D;S-U	
Stowage category		A	
			•

14.6 Special precautions for user

Precautions No special measures are necessary.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC not applicable

Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Decopaint regulation not relevant

Carcinogenic hazardous sub-

No

stance as per Annex II GefStoffV

Restriction of occupation. Persons already sensitised to diisocyanates may develop allergic reac-

tions when using this product.

Commercial Product Name: Fire Stop Gun Foam

Revision date: 10.12.2020 Print date: 10.12.2020 Version: 3.0/en

Persons suffering from asthma, eczema or skin problems should avoid

fischer 🖘

contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 accord-

ing to standard EN 14387) is used.

15.2 Chemical safety assessment

For this preparation a chemical safety assessment has been carried out. Safety assessment

> This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2,

8, 9, 12, 15 and 16 of this safety data sheet.

This Safety Data Sheet is prepared according to Commission Regulation Additional regulations

> (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evalua-

tion, Authorisation and Restriction of Chemicals (REACH)

SECTION 16: Other information

Relevant H-phrases H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H280: Contains gas under pressure; may explode if heated.

H302: Harmful if swallowed. H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H335: May cause respiratory irritation. H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated ex-

posure.

Wording of the hazard classes Acute Tox.: Acute toxicity

Skin Irrit.: Skin irritation

Eye Irrit.: Serious eye irritation Skin Sens.: Skin sensitization

Carc.: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Flam. Gas: Flammable gas

Aerosol: aerosols

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Aerosol 1; H222 H229	Calculated
Acute Tox. 4; H302	Calculated
Acute Tox. 4; H332	Calculated

Commercial Product Name: Fire Stop Gun Foam



Revision date: 10.12.2020

Version: 3.0/en Print date: 10.12.2020

Classification	Evaluation	
Skin Irrit. 2; H315	Calculated	
Eye Irrit. 2; H319	Calculated	
Resp. Sens. 1; H334	Calculated	
Skin Sens. 1; H317	Calculated	
Carc. 2; H351	Calculated	
STOT SE 3; H335	Calculated	
STOT RE 2; H373	Calculated	

Recommended restrictions

None under normal processing.

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.