

TOGE TSM B

Adhesive screw anchor for fastening crash barriers

Steel, anti-corrosion coated, TOGE KORR
Corrosivity category C5 high



Item nr.	Designation	Bore \varnothing	Depth of drill hole h_1	Embedment depth of anchor h_{nom}	Max. thickness of fixture t_{fix}	Packing Unit
202 141 650	TSM B 14x165 M16x35 SW12	14 mm	100 mm	100 - 140 mm	35 mm	25
202 161 900	TSM B 16x190 M18x45 SW13	16 mm	100 mm	100 - 160 mm	60 mm	25
202 162 200	TSM B 16x220 M18x45 SW13	16 mm	100 mm	100 - 160 mm	90 mm	25

Composite Mortar CF-T 300V

Chemical special mortar
Vinylester styrolfree, suitable for
concrete screws



Product overview

Item nr.	Designation	Packing Unit
222 222 003	Cartridge CF-T 300V	1
222 223 001	Mixing nozzle for CF-T 300V	1
222 222 004	Squeezing pistol for CF-T 300V	1

Processing Instructions

Temperature in ground	Processing time	Min. curing time in dry borehole	Min. curing time in wet borehole
$\geq -5^{\circ}\text{C}$	60 min	360 min	720 min
$\geq 0^{\circ}\text{C}$	60 min	180 min	360 min
$\geq 5^{\circ}\text{C}$	60 min	120 min	240 min
$\geq 10^{\circ}\text{C}$	45 min	80 min	160 min
$\geq 20^{\circ}\text{C}$	15 min	45 min	90 min
$\geq 30^{\circ}\text{C}$	5 min	25 min	50 min
$\geq 35^{\circ}\text{C}$	4 min	20 min	40 min