

# SPIT PULSA 65



In accordance to:  
 EN 15895-1  
 EN ISO 8662-11  
 Directive tool :  
 2012/19/EC  
 2011/65/EC  
 2006/42/EC  
 2004/108/EC  
 1999/5/EC  
 Aerosol Dispenser Directive: 75/324/EC  
 Battery:2006/66/EC  
 Charger:2014/35/EU  
 CEM 2014/30/EU

## Tool Specifications

Name	SPIT PULSA 65
Impact force (Joules)	107
Weight (kg)	4.1 (with battery)
Overall dimension LxH (mm)	404x113x362
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 65 mm in strip

## Characteristics

Drywall pin guide
Fully automatic tool (1000 shots per hour)
30 pins magazine (10 per strip)
Low push down force (4.5 kg)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 105 mn (25 mn = 1000 pins)
Fuel cell: 600 shots (20 °C), battery: up to 10000 shots

## Safety Specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 15895-1 : LpA,1s,1m=95dB(A) / Lp Cpeak=135 dB
Vibration, EN ISO 8662-11: 4.4 m-s <sup>-2</sup>

Accessories	Consumables
30 pins magazine	C6, HC6,UP6
Cleaning kit	