

spit

PULSA 40P+

Powerful Cordless Gas Nailer

For fixing drywall track into concrete,
steel & masonry



3 *spit*
YEAR
WARRANTY

NEVER STOP BUILDING

FAST, ACCURATE AND REPEATABLE FIXINGS



Maximise your productivity with the NEW PULSA 40P+. This cordless gas nailer for drylining first fix applications into concrete, steel and masonry is one of the fastest, most durable and reliable tools in the market.

WORK FASTER

Eight times faster than conventional drill and fix, the PULSA 40P+ has been specifically designed for dryliners wanting to save time and make money. Nail faster, for longer with a powerful, market-leading 3.7-volt Lithium-ion cell battery, capable of delivering 400% more fixes between charges than non-gas alternatives.

EXTENDED WARRANTY

Thanks to advances in technology and the highest quality components, the PULSA 40P+ comes with an extended 3-year warranty as standard.

INCREASED POWER

- An excellent stick rate in the hardest materials and up to 16% more powerful with gas technology

LIGHT TOOLS MAKE LIGHT WORK

- Up to 15% lighter than battery alternatives

OPERATE AT OPTIMUM SPEED FOR LONGER

- Up to 400% more fixes between charges than battery motor alternatives

WORK MORE, CHARGE LESS

- Extra battery capacity permits the tool up to 3500 shots per charge

3 YEARS WARRANTY AS STANDARD

- Improved engineering and increased robustness means an extended three year warranty

SLIM AND STREAMLINED

- Compact to access the tightest locations and benefit from a great line of sight

DEPTH OF DRIVE ADJUSTMENT

- For the perfect fix

ON SITE TOOL MAINTENANCE

- Easy to self maintain on site

LOW ACTUATION FORCE

- Work faster and easier, feel less fatigue



A GAS NAILER MADE SPECIFICALLY FOR DRYWALL PROFESSIONALS



APPLICATIONS

DRYWALL TRACK:

Fit metal head, foot and wall track to steel or concrete, masonry or block substrate quickly and reliably.



TIMBER:

Fix timber up to 20mm thick to concrete and structural steel, quicker than with conventional fixing methods.



FIRE PROTECTION SYSTEMS:

Fix fire protection systems to steel, quickly and with precision.

ANGLE BRACKETS:

Attach angle brackets to concrete, block, brick and structural steel with ease.



EML (Expanded Metal Lath):

Fix EML to all structural substrates, using 25mm washers and a magnetic pin guide.

SUBSTRATES



TECHNICAL SPECIFICATION

Code: (with 20 pin magazine)	019653
Weight with battery:	3.8kg
Pin range:	15-40mm Collated
Magazine capacity:	20 or 50 pin option
Intermittent operation:	2 pins per sec
Fuel cell life:	600 shots
Fixings per Battery Charge:	3,500

TOOL INCLUDES

- Palsa 40P+
- High impact carry case
- 1x battery
- All in one charger
- Safety glasses to EN166:F
- Single shot cover guard
- Instructions manual
- Allen key
- Safety instructions
- CE Declaration of Conformity



CONSUMABLES

10 strip collation + 1 x Fuel Cell

C6 PINS STANDARD CONCRETE (C25) Use in Standard Applications



Description	Length (mm)	Colattion Colour	Box Quantity	Code
C6 20	20	Black	500	057540
C6 25	25	Black	500	057541
C6 30	30	Black	500	057542
C6 35	35	Black	500	057543
C6 40 FH	40	White	500	057544

Suitable for use in 20 and 50 pin magazines.

HC6 PINS HARD CONCRETE (>C25) & STEEL Use in harder substrates with higher aggregate contact



Description	Length (mm)	Colattion Colour	Box Quantity	Code
HC6 15	15	Orange	500	057550
HC6 17	17	Orange	500	057551
HC6 22	22	Orange	500	057552
HC6 27	27	Orange	500	057553
HC6 32	32	Orange	500	057554

Suitable for use in 20 and 50 pin magazines.

STEEL WASHERS FOR USE WITH MAGNETIC PIN GUIDE

Description	Diameter (mm)	Box Quantity	Code
Steel Washer	25	1,000	011204

For use with Magnetic Pin Guide: 014641 - Palsa 40.



ACCESSORIES

Description	Quantity	Code
Magnetic Pin Guide (for use with 25mm Washers)	1	014641
Flat Magnetic Pin Guide	1	014642
50 Pin Magazine	1	019683
20 Pin Magazine	1	019337
All-in-one Li-ion Battery Charger	1	019614
3.7V 2.2Ah Li-ion Battery	1	019996
Palsa 40E Pin Guide	1	018423
Palsa 40P Pin Guide	1	018424
Palsa 40 Blister Pack (2 x Fuel Cells)	1	011773
Impulse/Palsa Cleaning Kit	1	013690
Impulse Cleaner 300ml	1	115251
Impulse Lubricating Oil	1	401482



50 Pin Magazine (019683)



Magnetic Pin Guide - for 25mm washers (014641)



Battery (019996)

PIN SELECTION GUIDE

Substrate	Track	Part to be fixed (mm)					EML
		5	10	15	20	27	
 Steel	HC6 15	HC6 15	HC6 17	HC6 22	HC6 27	HC6 32	HC6 15
 Hard Concrete C40/50 > C50/60	HC6 17	HC6 22	HC6 27	HC6 32	HC6 32	-	HC6 15-17
 Concrete & Brick	HC6 22 C6 20-25	HC6 22-27 C6 25	HC6 27-32 C6 25-30	HC6 32 C6 35	- C6 35-40	- C6 40	HC6 17-22 C6 25

Steel Support Material:

Min Thickness = 6.5mm - Recommended static load = 150 kg max

Concrete:

Recommended static load = 10 kg max (C20-25)

These figures are to guide you. Always check the suitability of calculations on a site-by-site basis.

spit

PULSA40P+



CONTACT INFORMATION

For training inquiries,
customer services & support:
cbu@itwcp.com
0800 833 381

For technical assistance:
www.spit.com
+44 (0)141 342 1660