

BPEM-T



BPGM-T construction materials & metal

RESCRIPTION: A turbo rim blade with special cooling holes and a reinforced flange centre for increased stability, blade cooling and less chipping. Fast cutting with long life.

USE ME FOR: Indian stone / Granite / House bricks / Class A Engineering bricks
Clay products / All reinforced concrete types / Ferrous metal sections up to 5mm gauge
Concrete kerbs, beams, lintels & flags / Occasional use in asphalt & abrasive materials

VERY FAST CUTTING WITH LONG LIFE

10MM CONTINUOUS TURBO RIM

VENTILATED CORE / SINTERED BOND

VENTILATED & REINFORCED FLANGE

INCREASED STABILITY / LESS CHIPPING



Self cooling











* 300mm AVAILABLE AS PART OF A TWIN PACK

MATERIAL TYPE

GLASS / REINFORCED PLASTIC

MULTIPLE APPLICATIONS

HAKE!	
#NSE	
VATERIAL	
_	

GLASS / REINFURGED PLASTIC	
POLYURETHANE	
FIBREGLASS	
MARBLE - DRY CUTTING	
STEEL BARS, PIPE & SECTIONS	
SG & GREY IRON	
PORCELAIN & HARD TILES	
CERAMIC TILES	
INDIAN STONE	
GRANITE	
SLATE	
CLASS A ENGINEERING BRICKS	
CLAY PAVIORS / PIPES / TILES	
FLINT AGGREGATE PRODUCT	
CLASS B ENGINEERING BRICKS	
HEAVILY REINFORCED CONCRETE	
MEDIUM REINFORCED CONCRETE	
LIGHTLY REINFORCED CONCRETE	
CONCRETE	
HARD YORK STONE	
QUARTZITE	
LONDON BRICK	
HARD CONCRETE PRODUCTS	
KERBS / LINTELS / BEAMS	
CAST PIPES	
BRICKS / CONCRETE FLAGS	
HAND MADE BRICKS	
FACING BRICKS	
CONCRETE ROOF TILES	
SOFT CONCRETE PAVIORS	
SAND BASED PAVIORS	
GREEN CONCRETE	
CEMENT SCREED	
LIGHTWEIGHT CONCRETE BLOCK	
HOT ROLLED ASPHALT	
ABRASIVE SAND / GRITSTONE	
ASPHALT OVER CONCRETE	
ASPHALT	
ABRASIVE MORTAR	

MULTIPLE APPLICATIONS: CONSTRUCTION	PLUS
DIMENSIONS	DPCM-T
(4½") 115 x 22.20 mm	115DPCM-T
(5") 125 x 22.20 mm	125DPCM-T
(9") 230 x 22.20 mm	230DPCM-T ∞
(12") 300 x 20.00 mm	300DPCM-T ∞
(14") 350 x 20.00 mm	350DPCM-T ∞

CONTINUOUS TURBO RIM


If a diamond blade has a continuous turbo rim then there will be less chipping than with segmented blades and faster cutting due to the castellation of the rim. This clears debris quicker and keeps the blade cool by trapping air in motion.



THE PRO-LINE FROM DURO, OFFERING
PROFESSIONAL LEVEL TOOLS AT VERY
COMPETITIVE PRICE LEVELS. THIS RANGE IS
RENOWNED FOR OFFERING GREAT QUALITY,
PERFORMANCE AND VALUE TOOLS WITH VERY



Cooling holes in a blade as the description says, will keep the steel core cool and will prevent distortion of that core. Keeping the diamond matrix cool in segments will improve speed and life.



REINFORCED FLANGE

A reinforced flange gives the diamond blade more stability under extreme use and keeps the steel core in line, therefore giving a cleaner, straighter cut.





HIGHLY SUITED

SOFT

NOT SUITABLE

SUITABLE WITH RESERVATIONS