

Timberfix

Fasteners designed to fix timber to steel. The Timberfix range first drill a clearance hole through the timber using the winged area of

this product, these wings break off when they come into contact with the steel allowing the drill point to drill the steel to the correct

size to give a very positive engagement every time.

This range is available in both 3 and 5 point versions allowing self drill action in steel up to 12.5mm thick.

APPLICATIONS

Fixing all grades of timber and plywood to hot and cold rolled steel. Dry wall self drill screw for plasterboard to studding

HEAD STYLES

Countersunk Phillips recess head No. 2 & 3. Heads are self embedding.

BENEFITS

Reamer wings produce a clearance thread through timber, breaking off as they hit the steel, giving a positive fix in thick and thin steel.

SPECIFICATIONS

Manufactured from Carbon Steel heat treated and bright Zinc plated 12 microns.

ASF78



5.5x110mm
No 5pt
Phillips 3

ASF77



5.5x85mm
No 5pt
Phillips 3

ASF67



5.5x60mm
No 5pt
Phillips 3

ASF270



5.5x109mm
No 3pt
Phillips 3

ASF269



5.5x85mm
No 3pt
Phillips 3

ASF261



5.5x60mm
No 3pt
Phillips 2

ASF260



4.8x50mm
No 3pt
Phillips 2

ASF79



4.8x38mm
No 3pt
Phillips 2

ASF71



4.2x25mm
No 3pt
Phillips 1

Other stock sizes
5.5x38, 55
4.8x32, 45
6.3x45, 55, 70

DRY WALL SCREWS

ASF93



5.5x42mm
No 3pt
Phillips 1

ASF92



5.5x34mm
No 3pt
Phillips 1

ASF91



5.5x25mm
No 3pt
Phillips 1

Additional sizes available up to 70mm. Also available with sharp point.